

Main Feature

3600mAh polymer Li-ion Battery	CTCSS/DCS non-standby code	10 Watt ultra-high output power	Voice companding function
COMP/Scrambler	Battery save function	1750Hz tone	Time-out-timer(TOT)
Side-key assignment	Busy channel lock	VOX transmitting	Scanning

Genneral

Frequency Range	UHF: 400-520MHz/VHF: 136-174MHz	Battery capacity	3600mAh
Channel capacity	16	Output power	High: 10W/Low: 5W
Operating Voltage	7. 2V DC	Antenna Impedance	50 ohm
AWorking Temperature	−20° C~+50° C	Frequency Stability	12. 5kHz/25kHz
Dimension (Exclude antenna)	133x59x36mm	Weight(Include Battery)	272g

Transmitter

Working mode	Simplex or semi-duplex
Modulation type	16KF¢3E
Spurious radiation	<=7. 5μ W
Modulated noise	<-40dB
Modulation distortion	<55
Frequency stability	5ppm
Max Fr. Deviation	<=±5kHz
Current	<=2600mA
Audio response	+6. 5——14dB
Adjacent Ch. Power	>=65dB
Intermediation sensitivity	8-12mv

Receiver

<=0. 2V
<=16kHz
>=65dB
>=55dB
1W
<=5%
5ppm
80mA(when standby)
220mA (when working)

Standard Accessories













User's Manual

Optional Accessories

More optional caaessories please refer to our website : www.retevis.com













Acoustic Tube headset





Throat mic





6 in 1 programming cable kit





Antenna