

RT26

RETEVIS



10W

high power output

- 10W
- VOX
- SCAN
- Low-battery alert
- Battery save
- Time-out-timer(TOT)

RT26

- / Battery save
- / Low-battery alert
- / 10W high power output
- / High /Low power switch
- / Scan function
- / VOX function
- / Emergency alarm
- / Time-out-timer(TOT)
- / Busy channel lockout(BCL)
- / End-tone elimination
- / Short cut operation Wide/Narrow band
- / Monitor /Monitor momentary function



Specification

General

Mode	RT26	Operating Voltage	7.4V
Frequency range	400-470MHz	Battery capacity	3000mAh
Channel capacity	16	Antenna impedance	50 Ω
Output power	High:10W Low:5W	Operating temperature	-20°C ~ +50°C
Channel spacing	25/12.5KHz	Dimensions (with battery,without antenna)	126*63*39mm/4.96*2.48*1.54in
Frequency stability	±2.5ppm	Weight (with antenna&battery)	300g/10.58oz

Transmitter

Modulation	F3E
Audio distortion	≤5%
Maximum deviation	≤5KHz

General

Sensitivity	0.25μV
Rated Audio	400mW
Rated Audio Distortion	≤5%

Standard Accessories



Adapter



Belt Clip



Antenna



Sling



Battery



Charger



User's manual

RETEVIS

kam@retevis.com www. retevis .com
SHENZHEN RETEVIS TECHNOLOGY CO.,LTD

