# RT93

RETE/15

(mobile piggyback)
Digital private network base station

### Feature:

- The intuitive status panel: The host panel comes with various status indicators and interface identifiers, which is very User-friendly.
- Dual time slot channel: Support standard DMR dual-slot working mode.
- Channels supported: Up to 1024 channel switching with PC tools.
- Adjustable transmit power: The transmit power can be adjusted according to actual needs, from 1 to 25 watts.
- Flexible IP networking: The device is connected in an IP interconnection mode, and supports wired access mode or wireless access modes such as WIFI, 3G/4G, and satellite communication to implement voice and data communication.
- Powerful scheduling management: Scheduling platform can implement scheduling management functions such as device management, terminal management, group logical allocation, and voice scheduling.



## RT93

(mobile piggyback) Digital private network base station

#### Transmitter:

| Output power:            | 1~25WContinuous adjustable |                    |                |
|--------------------------|----------------------------|--------------------|----------------|
| FM modulation Mode:      | 11KOF3E@12.5KHz            | 14KOF3E@20KHz      | 16KOF3E@25KHz  |
| 4FSK digital modulation: | 12.5KHz                    | Only data: 7K60FXD | Data and voice |
| Transmit Spurious:       | -36dBm<1GHz                | -30dBm>1GHz        |                |
| Modulation limit:        | ±2.5KHz@12.5KHz            | ±4KHz@20KHz        | ±5KHz@25KHz    |
| FM Noise:                | 40dB@12.5KHz               | 43dB@20KHz         | 45dB@25KHz     |

#### Receiver:

| Sensitivity:                  | Analog  Digital   | 0.3μV (12dB SINAD) 0.22μV (Typical) (12dB SINAD) 0.3μV (20dB SINAD) 0.3μV/BER5% |  |
|-------------------------------|---|---|--|
|                               | 0.000 Carlotte (1000 |   |  |
| Adjacent channel selectivity: | TIA603  | 65dB@12.5KHz/75dB@20/25KHz  |  |
|                               | ETSI  | 60dB@12.5KHz/70dB@20/25KHz  |  |
| Intermediation                | TIA603  | 75dB@12.5/20/25KHz  |  |
|                               | ETSI  | 70dB@12.5/20/25KHz  |  |
| Spurious Response             | TIA603  | 75dB@12.5/20/25KHz  |  |
|                               | ETSI  | ≥70dB@12.5/20/25KHz   |  |
| Block                         | TIA603  | 90dB  |  |
|                               | ETSI  | 90dB 84dB   |  |

#### Package includes:

- 1 x RT93 piggyback digital private network base station
- 1 x Backpack
- 1 x 450MHz antenna
- 1 x 4G Antenna
- 1 x GPS antenna
- 1 x WIFI antenna
- 1 x Power cable
- 1 x User Manual





# CE F© RoHS



### Shenzhen Retevis Technology Co.,Ltd

Add: 7/F, 13-C, Zhonghaixin Science&Technology Park, No.12 Ganli 6th Road, Jihua Street, Longgang District, Shenzhen, China

Web: www.retevis.com E-mail: kam@retevis.com Facebook: facebook.com/retevis



MADE IN CHINA