

RB75

GMRS Two Way Radio

RETCVIS

Feature:

- CTCSS/DCS function
- Power saving automatically
- Time-out-Time(TOT) function
- Scan function
- Squelch level
- Monitor
- VOX
- Voice chip DSP
- Waterproof function (IP67)
- Companding
- Programmable define



RB75

GMRS Two Way Radio

General

Frequency Range:	FRS:462.5500-467.7125
Memory Channel:	30CH
Operation Voltage:	DC 7.4V
Battery Capacity:	4500 mAh
Operating Temperature:	-20°C- + 50°C
Antenna Impedance:	50Ω

Transmitter

RF Output Power:	5W
Spurious Emission:	<-36dBm
Transmission current:	≤1.6A

Receiver

Receive Sensitivity:	-121dBm
Adjacent Channel Selectivity:	≥60dB
SNR:	>60dB
Rated Audio Distortion:	<3%
Receive Current:	≤300mA

Standard Accessories:

- 1 x RB75 Two Way Radio
- 1 x Battery Pack
- 1 x Belt Clip
- 1 x USB Drop-in Charging Tray
- 1 x Sling
- 1 x User Manual



CE FC RoHS



Shenzhen Retevis Technology Co.,Ltd.

Add: 7/F, 13-C, Zhonghaixin Science&Technology Park, No.12 Ganli
6th Road, Jihua Street, Longgang District, Shenzhen, China

Web: www.retevis.com

E-mail: kam@retevis.com

Facebook: facebook.com/retevis



MADE IN CHINA